

Raise3D DF2 Technical Specifications

The Raise3D DF2 solution is a Digital Light Printing (DLP) system offering speed, quality, exceptional reliability and efficient workflow via RFID. It is designed for engineering prototyping, manufacturing aids, and low-volume production using a wide variety of high-performance resins.

Printer	Raise3D DF2
Printer Hardware	<p>Print Technology Digital Light Printing (DLP)</p> <p>Build Size (W × D × H) 200 × 112 × 300 mm (7.87 × 4.41 × 11.8 inch)</p> <p>XY Resolution 2560 × 1440</p> <p>Max Part Weight 10 kg</p> <p>Max Printing Speed 25 mm/h (0.1 mm per layer)</p> <p>Layer Height 50-100 micron</p> <p>Resin Management Auto Resin Feeding, Resin Level Detection, Resin Confirmation</p> <p>Control Panel Touch Screen (Resolution: 1920 × 720) with Magic Layout (Allow to easily adjust the print layout and duplicate prints)</p> <p>RFID Print Platform Record the type of resin used and the printing, washing and curing settings</p> <p>Level Calibration Calibrated in factory</p> <p>Chamber Heating Max 40°C</p>
Resins	<p>Raise3D Resins Raise3D Standard White Resin, Raise3D High Detail Apricot Resin, Raise3D Tough 2K Grey Resin, Raise3D Rigid 3K Grey Resin, Raise3D High Clear Resin (Coming soon), Raise3D High Temperature Resin (Coming soon)</p> <p>Co-branding Resins with LOCTITE 3D IND405™, LOCTITE 3D PRO476™, BASF and Henkel Ultracur3D® RG 3280, Ultracur3D® RG 1100 B</p> <p>ORP (Open Resin Program) Coming soon</p>
Software and Network	<p>Connectivity Wi-Fi, LAN, USB port × 2, Live Camera</p> <p>Network Ethernet, Wireless 802.11 b/g/n</p> <p>Slicing Software ideaMaker (Features: Antialiasing; Auto Support; Auto Orientation; Auto Cross Section Analysis; Contour Compensation; Suction Cup Detection; Hollow; Drainage Hole; Texture Generation; Smaller Gcode Size)</p> <p>Remote Management Software RaiseCloud (Coming soon)</p> <p>Supported File Types STL/ OBJ/ 3MF/ OLTP</p> <p>Supported OS WINDOWS/ macOS/ LINUX</p>
Operation and Shipping	<p>Power Supply Input 100-240 V AC, 50/60 Hz 230 V @ 3.3 A</p> <p>Operating Ambient Temperature 15 - 30°C, 10 - 90% RH Non-Condensing (HOLD)</p> <p>Storage Temperature -25 to 55°C, 10 - 90% RH Non-Condensing (HOLD)</p> <p>Machine Size (W × D × H) 450 × 400 × 730 mm (17.7 × 15.7 × 28.7 inch)</p> <p>Net Weight 40 kg (88.2 lbs)</p> <p>Gross Weight 59.4 kg (131 lbs)</p> <p>Shipping Dimensions 710 × 595 × 980 mm (28.0 × 23.4 × 38.6 inch)</p>

Raise3D DF Wash & DF Cure Technical Specifications

The Raise3D DF2 solution is a Digital Light Printing (DLP) system offering speed, quality, exceptional reliability and efficient workflow via RFID. It is designed for engineering prototyping, manufacturing aids, and low-volume production using a wide variety of high-performance resins.

Wash	Raise3D DF Wash	
Wash Hardware	Washing Tank Volume	14 L
	Max Washing Size	200 × 112 × 300 mm (7.87 × 4.41 × 11.8 inch)
	Compatible Solvent	IPA
	Washing Features	Twin-turbo Washing, Hand Washing Simulation
	Drying Feature	Double Fan Air Drying
	Drainage	Automatic Liquid Drainage with Waste Container
	Wash Profile	RFID Auto Set or Manual Entering
Operation and Shipping	Power Supply Input	100-240 V AC, 50/60 Hz, 96 W
	Operating Ambient Temperature	10°C-35°C
	Storage Temperature	-25 to 55°C, 10 - 90% RH Non-Condensing (HOLD)
	Machine Net Weight	27.7 kg (61.1 lbs)
	Machine Gross Weight	45.8 kg (101 lbs)
	Waste Container Net Weight	0.7 kg (1.54 lbs)
	Waste Container Gross Weight	1.5 kg (3.3 lbs)
	Machine Size (W × D × H)	400 × 410 × 646 mm (15.7 × 16.1 × 25.4 inch)
	Waste Container Size (W × D × H)	350 × 190 × 290 mm (13.8 × 7.5 × 11.4 inch)
	Machine Shipping Dimensions	725 × 585 × 915 mm (28.5 × 23.0 × 36.0 inch)
Waste Container Shipping Dimensions	407 × 247 × 349 mm (16.0 × 9.7 × 13.7 inch)	

Cure	Raise3D DF Cure	
Cure Hardware	Max Curing Size	φ 230 × 300 mm (φ 9 × 11.8 inch)
	Curing Source	LED (365nm, 385nm, 405nm mixed); Max Air Heating Temperature up to 120°C
	Cure Profile	RFID Auto Set or Manual Entering
Operation and Shipping	Power Supply Input	100-240 V AC, 50/60 Hz, 500 W
	Operating Ambient Temperature	10-35°C
	Storage Temperature	-25 to 55°C, 10 - 90% RH Non-Condensing (HOLD)
	Net Weight	32.8 kg (72.3 lbs)
	Gross Weight	49.2 kg (108.5 lbs)
	Machine Size (W × D × H)	490 × 400 × 610 mm (19.3 × 15.7 × 24.0 inch)
Shipping Dimensions (W × D × H)	725 × 585 × 850 mm (28.5 × 23.0 × 33.5 inch)	