

VisiJet® M2E-BK70

Revision Date: March 6, 2020

1. IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Identification of the mixture: VisiJet M2E-BK70

1.2 Use of the preparation: For use with ProJet® 2500 systems

1.3 Company/undertaking identification:

3D Systems, Inc.
333 Three D Systems Circle
Rock Hill, South Carolina U.S.A.
Phone: 803.326.3900 or
Toll-free Phone: 800.793.3669
e-mail: moreinfo@3dsystems.com
Chemical Emergency:
800.424.9300 – Chemtrec

3D Systems Europe Ltd. 200 Maylands Avenue Hemel Hempstead Herts, HP2 7TG United Kingdom Phone: +44 144-2282600

e-mail: moreinfo@3dsystems.com Chemical Emergency: +1 703.527.3887 - Chemtrec 3D Systems Asia-Pacific 30-32 Ceylon St Nunawading VIC 3131 Australia

+61 3 9819 4422 e-mail: moreinfo@3dsystems.com Chemical Emergency: +(61) 29037.2994 – Aus Chemtrec

1

2. HAZARDS IDENTIFICATION

2.1 Classification

GHS: Regulation (EC) No. 1272/2008, 29 CFR 1910, Australian Dangerous Goods Code:

Skin Corrosion/Irritation	Category 2 H315	
Serious Eye Damage/Eye Irritation	Category 1	H318
Skin Sensitization	Category 1	H317
STOT SE- Respiratory Irritation	Category 3	H335
Acute Toxicity (inhalation)	Category 4	H332
Toxic to aquatic life with long-lasting effects	Category 2	H411

2.2 Label Elements

Regulation (EC) No, 1272/2008:

Hazard pictograms and signal word:







GHS07

GHS05

GHS09

Signal word: Danger

Hazard determining components of labelling:

Contains: 2-Propen-1-one, 1-(4-morpholinyl); ethoxylated phenol monoacrylate; diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide

Hazard statements:

H315 Cause skin irritation

H317: May cause an allergic skin reactionH318: Causes serious eye damageH335: May cause respiratory irritation

H332: Harmful if inhaled

H411: Toxic to aquitic life with long lasting effects



VisiJet® M2E-BK70

Revision Date: March 6, 2020

Precautionary statements:

Prevention:

P260: Do not breathe dust/fume/gas/mist/vapors/spray.

P264: Wash contaminated skin thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P285: In case of inadequate ventilation wear respiratory protection.

Response:

P302 + P352: IF ON SKIN: Wash with plenty of soap and water

P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.

P362: Take off contaminated clothing and wash before reuse

P391: Collect spillage.

P362: Take off contaminated clothing and wash before reuse

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P307 + P311: IF exposed: Call a POISON CENTER or doctor/physician.

P391: Collect spillage.

Storage:

P410 + P403: Protect from sunlight. Store in a well-ventilated place.

Disposal:

P501 -Dispose of contents/container in accordance with local/state/regional regulations

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Chemical characterization: Description: Organic mixture

3.2 Dangerous components:

Chemical name	CAS-	EC-	%	Classification
2-Propen-1-one, 1-(4-morpholinyl)	number 5117-12-4	418-140-1	1-10	Regulation (EC) 1272/2008 Acute Toxicity (oral) Category 4 - H302 Serious Eye Damage/Eye Irritation Category 1 - H318 STOT repeat (Oral) Category 2 - H373
Ethoxylated phenol monoacrylate	56641-05-5	500-133-9	20-30	Skin Sensitization Category 1 - H317 Serious Eye Damage/Eye Irritation Category 2 - H319 Skin Corrosion/Irritation Category 2 - H315 STOT Single Exposure Category 3 - H335
2-Propenoic acid, 2-hydroxyethyl ester	52404-33-8	641-075-5	20-30	Serious Eye Damage/Eye Irritation Category 2 - H319 Skin Corrosion/Irritation Category 2 - H315 Skin Sensitization Category 1 - H317
Poly(oxy-1,2-ethanediyl), alpha hydro.omega[(1-oxo-2- propenyl)oxy]-, ether with 2-ethyl-2- (hydroxymethyl)-1,3propanediol (3:1)	28961-43-5	500-066-5	1-5	Serious Eye Damage/Eye Irritation Category 2 - H319 Skin Corrosion/Irritation Category 2 - H315 Skin Sensitization Category 1 - H317
A2-Propenoic acid, (1R,2R,4R)- 1,7,7trimethylbicyclo[2.2.1]hept-2-yl ester, rel-	5888-33-5	227-561-6	5-15	Skin Sensitization Category 1 - H317 Aquatic Chronic Category 2 - H411 Aquatic Acute Category 1 - H400
2-[[(butylamino)carbonyl]oxy]ethyl acrylate	63225-53-6	264-036-0	15-25	Acute Toxicity (inhalation) Category 3 - H331 Skin Sensitization Category 1 - H317 Aquatic Chronic Category 2 - H411
diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	75980-60-8	278-335-8	1-5	Reproductive Toxicity Category 2 - H361 Skin Sensitization Category 1 - H317

4. FIRST AID MEASURES

4.1 General Information: Ensure that eyewash stations and safety showers are close to the workstation location.



VisiJet® M2E-BK70

Revision Date: March 6, 2020

- **4.2 In case of inhalation:** May cause respiratory irritation. Move affected person to fresh air. If respiratory irritation occurs, if breathing becomes difficult seek medical attention immediately.
- **4.3 In case of skin contact:** May cause irritation or sensitization by skin contact, including redness and/or swelling. Immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse.
- **4.4 In case of eye contact:** Irritating to eyes. Causes redness, swelling and pain. Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms persist.
- **4.5** In case of ingestion: Irritating to mouth, throat and stomach. If ingested, drink plenty of water and seek immediate medical attention. Do not induce vomiting.
- **4.6 Self-protection of the first aider:** Put on appropriate protective equipment (see section 8). Move exposed person to fresh air. Remove contaminated clothing and shoes.

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media: Water mist, dry chemical, carbon dioxide, or appropriate foam.
- 5.2 Extinguishing media which must not be used for safety reasons: High volume water jet.
- 5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: Thermal decomposition products can include CO₂, CO, NO_x and smoke.
- **5.4 Special protective equipment for fire-fighters:** Wear full protective clothing, including helmet, self-contained positive-pressure or pressure demand breathing apparatus, protective clothing and facemask.
- **5.5 Additional information:** Move container from area if it can be done without risk. Cool containers with water spray. Avoid inhalation of material or combustion by-products.

6. ACCIDENTAL RELEASE MEASURES

- **6.1 Personal precautions:** Keep unnecessary personnel away. Wear appropriate protective equipment and clothing. Consult expert immediately.
- **6.2 Environmental precautions:** Stop the flow of material, if this is without risk. Ventilate contaminated area. Eliminate sources of ignition. In case of contamination of aquatic environment inform local authorities.
- **6.3 Methods for cleaning up:** Wear appropriate protective equipment and clothing to minimise exposure. Use of certified respirators and chemical resistant gloves are required to avoid exposure to any unreacted materials during spill clean-up (use of a 3M 6000 respirator with organic vapor cartridge A2 or half mask 3M 4251 is recommended).

Absorb spillage with suitable absorbent materials. Place all waste in an appropriate air tight bags or containers for disposal. The material and its container must be disposed of as hazardous waste. Keep away from sources of ignition.

7. HANDLING AND STORAGE

- **7.1 Handling** Provide adequate ventilation. Use suitable protective equipment. Avoid contact with skin and eyes. Do not breathe vapors or mist. Avoid ignition sources. Do not allow to enter drains or watercourses.
- **7.2 Storage:** Store sealed in the original container at room temperature. Keep this material indoors in a cool, dry, well ventilated place. Store out of direct sunlight or UV light sources. Storage Temperature: below 35 °C / 95 °F. Storage class 10, environmentally hazardous liquids.



VisiJet® M2E-BK70

Revision Date: March 6, 2020

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure limit values:

General Product Information: No occupational exposure limits (PEL/TWA) have been established for this product.

8.2 Exposure controls

Technical measures to prevent exposure: Use only with machines that have exhaust ventilation capability. Make sure that the carbon filtration at the exhause working properly.

Instructual measures to prevent exposure: When using, do not eat, drink or smoke. Wash hands after handling and before eating, smoking and using the lavatory and at the end of the day.

Personal protection equipment:

Respiratory protection: Recommend to establish engineering controls measures, such as local exhaust

ventilation, to the printing rooms and post processing areas to minimize inhalation exposure.

Hand protection: Use impervious nitrile gloves.

Eye protection: Wear safety glasses or chemical goggles.

Body protection: Use apron and closed shoes.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance: Physical state: liquid Colour: light yellow Odour: mild acrylate

9.2 Important health, safety and environmental information

pH (20 °C): NA
Melting point/range (°C): NA
Boiling point/range (°C): NA

Flash point (°C): 107.5 (Pensky-Martens closed cup)

Ignition temperature (°C):

Vapour pressure (°C):

NA

Density (g/cm3):

NA

Bulk density (kg/m3):

Water solubility (20°C in g/l):

Partition coefficient:

NA

n-Octanol/Water (log Po/w):

NA

Viscosity, dynamic (mPa s): 800 - 1000 (@ 30 °C)

Dust explosion hazard: NA Explosion limits: NA

10. STABILITY AND REACTIVITY

- **10.1 Conditions to avoid:** Avoid exposure to heat and light. Take necessary actions to avoid static electricity discharge.
- 10.2 Materials to avoid: Oxidizing materials, strong acids and strong bases.
- **10.3 Hazardous decomposition products:** Carbon dioxide, carbon monoxide and other toxic fumes can be released at high temperatures or upon burning.

11. TOXICOLOGICAL INFORMATION

11.1 Toxicokinetics, metabolism and distribution: NA



VisiJet® M2E-BK70

Revision Date: March 6, 2020

11.2 Acute effects (toxicity tests) - Formulation has not been tested

Acute toxicity of the components:

Irritation to skin and eye Causes sensitisation Corrosive to skin

- **11.3 Experiences made in practice:** Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- **11.4 General remarks:** Carcinogenicity: None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

12. Ecological information

- **12.1 Ecotoxicity:** The aquatic toxicity of the product is unknown; however based on components, it is predicted that this material may be harmful to aquatic organisms or cause long-term adverse effects in the aquatic environment. Prevent contamination of soil, drains and surface waters.
- 12.2 Mobility: No information available for product.
- 12.3 Persistence and degradability: No information available for product.
- 12.4 Results of PBT assessment: No information available for product
- 12.5 Other adverse effects: No information available for product

13. DISPOSAL CONSIDERATIONS

- **13.1 Appropriate disposal / Product:** Do not contaminate drains, soil or surface waters with this material or its container. Reduce waste by attempting to utilize product completely. Dispose of this container and its contents in accordance with all local, state, and federal regulations. Do not reuse or refill.
- 13.2 Waste codes / waste designations according to EWC / AVV: 070208
- 13.3 Appropriate packaging: NA
- **13.4 Additional information:** Prior to disposal 3D Systems recommends consulting an approved waste disposal firm to ensure regulatory compliance.

14. TRANSPORT INFORMATION

14.1 Land transport (DOT/ADR/RID/GGVSE):

UN Number: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. Technical name: (Acrylates)

Class: 9 Packaging group: III

Marine pollutant : yes Contains: Acrylates

14.2 Sea transport (IMDG-Code/GGVSee):

UN Number: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. Technical name: (Acrylates)

Class: 9 Packaging group: III

Marine pollutant : yes Contains: Acrylates

14.3 Air transport (ICAO-IATA/DGR):

UN Number: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. Technical name: (Acrylates)

Class: 9 Packaging group: III

Marine pollutant : yes Contains: Acrylates



VisiJet® M2E-BK70

Revision Date: March 6, 2020

14.4 US Department of Transportation (DOT)

UN Number: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. Technical name: (Acrylates)

Class: 9 Packaging group: III

Marine pollutant : yes Contains: Acrylates

15. REGULATORY INFORMATION

15.1 EU regulations

EINEC/ELINCS/NLP: listed or exempt from listing

REACH Annex XVII: None listed

15.2 EU National regulations

Wassergefährdungsklasse (water hazard class, Germany): WGK 2: Hazard to waters

15.3 US FEDERAL

TSCA: All components listed or exempt from listing

Toxic Substances Control Act (TSCA) - 5(a)(2) Significant New Use Rule List of Chemicals:

Contains 2-Propen-1-one, 1-(4-morpholinyl) (CAS 5117-12-4) subjected to TSCA §5(a)(2) Significant New Use Rule at 40 CFR 721.5185

Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D):

Contains 2-Propen-1-one, 1-(4-morpholinyl) (CAS 5117-12-4). 0.1 % One-Time Export Notification only

SARA 302 EHS List (40 CFR 355 Appendix A): None listed

SARA 313 (40 CFR 372.65): None listed

CERCLA (40 CFR 302.4): None listed

SARA 302 EHS List (40 CFR 355 Appendix A): None listed

SARA 313 (40 CFR 372.65): None listed CERCLA (40 CFR 302.4): None listed

15.4 International regulations: All components of this product are registered or exempt from registration according to chemical regulations in Australia, Canada (DSL or NDSL), China, Japan ENCS Japan ISHL, Taiwan,

New Zealand, South Korea, Switzerland, and Philippines chemical inventories.

15.5 Japanese regulations

Chemical Risk Information platform (CHRIP) listed

Industrial Health and Safety Law not applicable
Hazardous material not applicable
Organic solvent poison prevention rule
Ordinance on prevention of hazard due to not applicable

specified chemical substances
Lead Poisoning Prevention Rule
Poison and Deleterious Substance Control law
not applicable

PRTR and Promotion of Chemical Management no listed components

law (PRTR Law)

Fire Services Act Category 4, Class 3, oil

Explosives Law not applicable
High pressure gas safety law not applicable
Export Trade Control Order not applicable

Waste Disposal and Public Cleaning Law applicable. Before disposal, consult an approved waste disposal operative to ensure regulatory compliance.



VisiJet® M2E-BK70

Revision Date: March 6, 2020

16. OTHER INFORMATION

16.1 Relevant Hazard Statements (number and full text) referred to in sections 2 and 3 (according to (EC) No. 1272/2008):

H302: Harmful if swallowed

H318: Causes serious eye damage

H315: Causes skin irritation

H400: Very toxic to aquatic life

H319: Causes serious eye irritation

H315: Causes skin irritation

H361f: Suspected of damaging fertility or the unborn child

H335: May cause respiratory irritation

H373: May cause damage to organs through prolonged or repeated exposure

H401: Toxic to aquatic life

H317: May cause an allergic skin reaction

H411: Toxic to aquatic life with long-lasting effects

16.2 Further information:

SDS Creation Date: March 6, 2020

SDS Revision #:-00-A

SDS Revision Date:...... Reason for Revision:

www.3dsystems.com

800.793.3669 (Toll-free in the US GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.) 803.326.3900 (Outside the U.S. GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.) +44 144-2282600 (Europe GMT+01:00; Mon – Fri, 08:00 a.m. - 17:00 p.m. MEZ)

DISCLAIMER OF LIABILITY: The following supersedes any related provision in your company's forms, letters, and agreements from, by or with 3D Systems Corporation. 3D Systems, Inc. makes no warranty whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall 3D Systems, Inc. be liable for incidental, consequential, or other damages from alleged negligence, breach of warranty, strict liability or any other theory, arising out of the use or handling of this product. The sole liability of 3D Systems, Inc. for any claims arising out of the manufacture, use or sale of its products shall be for the buyer's purchase price.

The contents of this safety data sheet are subject to change without notice. 3D Systems, Inc. recommends that you periodically check www.3dsystems.com to make sure you are using the most current safety data sheet.

© Copyright 2020 by 3D Systems, Inc. All rights reserved. The 3D logo, ProJet and VisiJet are registered trademarks of 3D Systems, Inc.